



BRICKFORM® Antique Release™/ Efflorescence Remover™

Concrete cleaner

BRICKFORM Antique Release/Efflorescence Remover is a safer, more-pleasant product for use in cleaning concrete-type surfaces than Muriatic acid. It is perfect for the removal of excess BRICKFORM Antique Release or for the removal of efflorescence.

PRODUCT DESCRIPTION • BRICKFORM Antique Remover is a blend of acids and surfactants. It is completely biodegradable and contains no toxins or carcinogens. BRICKFORM Antique Release/Efflorescence Remover is corrosive and should be handled with care.

USES • BRICKFORM Antique Release/Efflorescence Remover can be used to remove excess powdered release that has been embedded during the imprinting process. It can also be used to remove efflorescence and to clean and brighten exposed-aggregate concrete and to remove cement scale (gray residue left after concrete has dried). Use on colored or uncolored, stamped or exposed aggregate concrete, porous brick, natural and manufactured stone, stucco, slate, unglazed tile and flagstone.

LIMITATIONS • BRICKFORM Antique Release/Efflorescence Remover does not clean or remove oil, grease, or rust stains.

PACKAGING • BRICKFORM Antique Release/Efflorescence Remover is available in one-gallon containers.

COVERAGE • BRICKFORM Antique Release/Efflorescence Remover will cover 200 to 800 square feet when used to remove BRICKFORM® Antique Release. Then using to remover efflorescence, the coverage will be 100 to 400 sq. ft. per gallon. Coverage will depend on the porosity of surface.

STORAGE • Store in a safe place. Keep containers tightly sealed. DO NOT allow product to freeze. Material that is frozen CANNOT be used when thawed. Shelf life is approximately 12 months.

CAUTION • CORROSIVE Contains Acid. KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Material Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Avoid contact with skin and eyes and clothing. Do not breathe vapor or mist. Wear acid vapor mask (NIOSH/MSHA TC 23C approved), goggles, rubber gloves, protective clothing and chemical-resistant apron and boots. Close container after each use. Use good hygiene when handling this product and wash and bathe after each use. Be sure to wash clothing after each use.

PREPARATION • BRICKFORM strongly recommends representative jobsite samples. Individuals who will be performing the work should test different sections of the concrete to determine suitability. BRICKFORM Antique Release/Efflorescence Remover is incompatible with chlorine bleaches, ammonia and most other cleaners, and cannot be used on most metals. For best results, the application area should be damp, but with no standing water. Any standing water should be removed with a squeegee or mop prior to application. BRICKFORM Antique Release/Efflorescence Remover is NOT RECOMMENDED for pre-sealed or dense surfaces, such as glazed tile, marble or granite, dense brick, dense slate, or terrazzo. If in doubt, test the surface by sprinkling with water. If water beads up on the surface, additional cleaning and testing must be done. Do not use where hydrostatic pressure is possible.

FEATURES

- Controlled Antique Release Removal
- Removes Cement-Scale
- Completely Biodegradable
- Apply With Brush or Sprayer

APPLICATION • Always test a small area for results prior to total job application.

Antique Release Remover Instructions: BRICKFORM Antique Release/Efflorescence Remover must be diluted one-to-one with water. After the product is diluted, it can be applied to the surface with a brush or low-pressure sprayer, brush, or watering can. A plastic garden-type pump sprayer is best. Commercial applicators should use a spray devise that will not create heavy misting. Let the material remain on the surface for 1 to 3 minutes or until all foaming action stops. Begin gently scrubbing the surface with a stiff-bristle brush until the desired removal is achieved. The surface must then be flushed with clean water and neutralized with a pH neutralizer such as ammonia, baking soda, or T.S.P. Remove water by mop squeegee, or wet-vacuum. The rinse water may be slightly corrosive and care must be taken to control runoff.

Efflorescence and Scale Removal Instructions: DO NOT DILUTE. Apply full-strength. Use a low-pressure sprayer, brush, or watering can. A plastic garden-type pump sprayer is best. Commercial applicators should use a spray devise that will not create heavy misting. Let the material remain on the surface for 1 to 3 minutes or until all foaming action stops. If the remover dries on the surface, re-apply. Scrubbing with a stiff wire brush may be necessary to remove heavy degrees of efflorescence or cement scale. Multiple cleanings may be necessary for concrete and masonry surfaces that contain large amounts of salts, lime, or alkalis. The surface must then be flushed with clean water and neutralized with a pH neutralizer such as ammonia, baking soda, or T.S.P. Remove water by mop squeegee, or wet-vacuum. The rinse water may be slightly corrosive and care must be taken to control runoff. When preparing a surface for sealing, additional cleaning with the appropriate cleaning solution may be necessary to remove grease, oil, or rust.

SEALING • After the concrete has been allowed to cure for 28 days, protect the surface with BRICKFORM Gemseal™ or BRICKFORM Polyseal™-High-Gloss Sealer, BRICKFORM Masterseal™-Abrasion-Resistant Sealer, or BRICKFORM Satinseal™-Water-Based, Semi-Gloss Sealer. Please get a copy of the appropriate Technical Information and Material Safety Data Sheet before attempting to use these products.

MAINTENANCE • The sealed surface should be inspected periodically for areas of thin or traffic-worn sealer and reapplied as needed.

WARRANTY • This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

ORDER SPECIFICATIONS

Product	BRICKFORM Antique Release/Efflorescence Remover
Shipping Weight	9.0 Lbs.
Container Size	1-Gallon
Item No.	ER-1