

PROLINE *DURACOLOR*

EZ-TIQUE

DESCRIPTION PROLINE *Duracolor* EZ-Tique Cementitious Antiquing Product is a versatile coloring agent that can be easily applied and will hold fast to any textured concrete surface. It is sold as a powder but is designed to be mixed with water and applied as a liquid wash coat. EZ-Tique can be used to revitalize a weathered concrete surface or add an antique color to a freshly textured surface. It goes on quickly and easily and can be removed readily for greater control of the coloring process. This product is water-based, non-hazardous, and zero V.O.C. It comes in 42 standard colors, matching the Proline *Duracolor* CH and AR Color Chart, and custom colors can be matched to order for no charge.

APPLICATION • PROLINE *Duracolor* EZ-TIQUE is easy to mix and apply so it can be used by professionals and do-it-yourselfers alike. It comes in a 1 gallon pail with approximately 3 pounds of colored powder and a three-quarter cup measuring spoon wrapped in a plastic bag. To mix: pull out and open the bag of EZ-Tique powder, fill the 1 gallon pail with water, and mix in one full three-quarter cup measuring spoon of the powder. Use more or less of the product in one gallon of water to achieve different results in color intensity. EZ-Tique can be mixed readily with a stir stick so motorized mixing is not necessary, but the product in the container will need to be agitated periodically during application to keep the solids from settling. This settling property of EZ-Tique is important in reaching the desired antique effect. Before applying product to unsealed concrete, it is helpful to pre-moisten the surface with water so the liquid color will have time to even out and settle properly. The most basic technique to apply EZ-Tique is to simply pour the liquid color straight onto the horizontal concrete surface with a standard garden watering can, making sure to leave a uniform coat of liquid over the area to be covered. If necessary, liquid EZ-Tique can be spread quickly and easily with a clean push broom. Be sure to have clean water handy to spray on the surface to make sure the color spreads uniformly. EZ-Tique can be cleaned up readily with water while it is still wet and can be wiped off with a clean dry sponge when dry.

COVERAGE • One 3 pound bucket of PROLINE EZ-Tique covers about 2000-3000 square feet.

STORAGE • Store in a cool, dry place in temperatures below 120°F. Shelf life is approximately one year, but will last much longer if containers are kept tightly sealed.

WARRANTY • This product is warranted to be of uniform quality within reasonable manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's appropriate applicability and assumes all risk and liability.

WARNING • THIS PRODUCT MAY CONTAIN A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. All concrete finishers and all onsite personnel must wear an OSHA-NIOSH approved dust respirator while applying or working around this product. Avoid contact with eyes and skin. Wear rubber gloves to protect skin and safety eye goggles. Before using this product, completely read the PROLINE *Duracolor* EZ-TIQUE *Technical Information Sheet* and MSDS. **KEEP OUT OF REACH OF CHILDREN.**

PROLINE CONCRETE TOOLS
2560 JASON CT. OCEANSIDE, CA 92056
(800) 795-4750

EZ-Tique

How-to guide

1



Measure and Mix with Water

2



Agitate

3



Apply with a soft bristle brush and let dry thoroughly

- Use on New and Existing concrete.
- Apply using different colors at the same time.
- Available in over 40 colors. Custom colors available.



For more information please contact us at:

1-800-795-4750

prolinestamps.com